

LCDP15TS

TOUCH SCREEN MONITOR

LCDP15TSR

MONITOR WITH CARD READER

TECHNICAL SPECIFICATIONS

15" TOUCH SCREEN
MONITOR WITH OPTIONAL
MAGNETIC STRIPE CARD
READER



FEATURES

- USB TOUCH SCREEN
- COUNTERTOP STAND
- WIDE VIEWING ANGLE
- OPTIONAL 3-TRACK MAG CARD READER
- OSD

LANGUAGE SUPPORT:

ENGLISH, GERMAN, FRENCH, SPANISH, RUSSIAN, and More...

MSR CARD READER

COLOR:	Black
USB CABLE LENGTH:	150cm
OPERATING LOCUS:	Indoor
CURRENT:	<45mA
READ TYPE:	1/2/3 Track, Manual Swipe
INTERFACE:	USB
STANDARDS:	ISO 7811
RESPONSE:	LED
FEED:	10-150 mc/sec Card Feed
DIMENSIONS (mm):	90(D) x 27(W) x 28(H)
POWER SUPPLY:	5VDC (supplied by host)
RATED:	800,000 Passes
APPLICATIONS:	POS, Security Contrl, CAT
GROSS WEIGHT:	0.2 kg
OPERATING TEMP:	0°C~60°C
STORAGE TEMP:	-20°C~80°C
OPERATING HUMIDITY:	10%~90%

SPECIFICATIONS

DISPLAY:	15" Color TFT LCD (4:3)
INPUT SIGNAL:	VGA
DOT FORMAT:	1024 x 768
BACK LIGHT:	LED
BRIGHTNESS RATING:	500 NIT
VIEWING ANGLE (L/R/T/B):	80°/80°/80°/80°
POWER REQUIREMENTS:	110~250VAC 50/60 HZ
INPUT:	15-PIN DSUB (VGA)
DIMENSIONS:	396 X 115 X 378MM
OPERATING TEMPERATURE:	-10°C ~ 60°C (+14°F ~ +140°F)
STORAGE TEMPERATURE:	-20°C ~ +70°C (-4°F ~ +158°F)
TOUCH SCREEN:	4-WIRE RESISTIVE
TOUCH SCREEN LIFE:	>50 MILLION
WEIGHT:	NW: 3.85KG, GW: 4.8KG

*Specifications subject to change without notice.

Miller Technologies
109 Fairytale Lane
Surf City, NC 28445

**Miller
Technologies**

Pho: (910) 328-2829
Fax: (910) 328-5494
Email: info@millertech.com

www.millertech.com